



850V Deep Vac model shown.



750V model shown.

FEATURES

- » An electric start ranging from 11 Hp engine to 21 Hp Honda engines and a 160 CFM (cubic feet per minute) to 230 CFM vacuum pumps. Units have a 650 gallon tank capacity (9,990 fully loaded weight) up to 800 gallons (12,480).
- » A good solution for operators who have pits deeper than 7' 6". The 750V pit cleaner operates efficiently at depths up to 10'. See our 850 Deep Vac for cleaning pits up to 15' deep.
- » These are an ideal pit cleaner for operators who have carwashes with limited access pits. These pits are often the secondary pits where cleaning access is available through a manhole or other small opening.
- » The 750 Vac can empty a typical 100 cubic foot sediment pit in about 40 minutes.
- » Easy to use and unload. The tank is dumped using a hydraulic lift system. The mud load is set free from inside the tank by using a pneumatic load breaker. Both the pneumatic load breaker and the hydraulic system are driven by the pit cleaner's engine with simple, easy-to-use controls.
- » The 750 Vac weighs in at 9,990 lbs fully loaded. This means it can be safely and legally pulled by a full size pick-up. Check your vehicle to see if it is rated to safely handle this conveniently sized unit.
- » We have had a Midwest car wash operator report that with a Ring-O-Matic pit cleaner, they can reduce their pit cleaning costs by over \$10,000 per year in their 19 bay operation. This gave them a very quick return on their investment.

VACUUM PIT CLEANER SERIES

FEATURES	750V	850V DEEP VAC
Engine	Electric start 11 Hp Honda with 3 year warranty	Electric start 21 Hp Honda OHV air cooled engine
Empty Weight	3,120 lbs.	3,600 lbs.
Trailer GVWR	9,990 lbs.	12,480 lbs.
Overall Trailer Dimensions	15' L x 6'¼" W x 7'H	20' L x 6'¼" W x 7'H
CFM	160 CFM	230 CFM
Inches of Vacuum	20" Hg	20" Hg
Dry Bag House Filtration	NA	Standard
Rear Door	1/2 Door	Hydraulic Full Opening
Tank Capacity	650 gallon/3.2 cu. yd.	800 gallon/3.9 cu. yd.
Height in Transport	7'H	7'H
Max Height in Operation	7'H	7'H
Max Digging Depth	10' below ground level	15' below ground level
Includes	2-5/16" ball hitch, jack, 235/80/R16 tires	2-5/16" ball hitch, jack, 235/80/R16 tires
Warranty	One year	One year
OPTIONS		
Strobe and Halogen Work Lights	Optional	Optional
Decanting Valve	Optional	Optional
Sight Eyes	Optional	Optional
Spare Hoses	Optional	Optional
Customer Logo on Tank Sides	Optional	Optional
Custom Paint Color	Optional	Optional
Alloy Wheels	Optional	Optional
Truck Mounting	Optional	Optional



750V model shown.



850V Deep Vac model shown.