



**INNOVATION
IN PRESERVATION**

M-Series™

**Crack Sealant
Melter Applicators**



M4 410



M2 230



M1 150

Redefining Productivity:

Cimline's new M1 and M2 crack sealers build on our fifty plus years of innovation. Known for reliability, performance and productivity, contractors rave about the operator ease of use in our Cimline M-Series™ crack sealers, which range from 150 to 410-gallons capacities. Simple and safe operation makes Cimline melter applicators the preferred pavement maintenance choice by contractors and municipalities alike.



Redesigned Trailer and Tank:

A temperature probe mounted inside the pump is now standard, as is a smaller cabinet to house the pump. Both of which results in better temperature control and performance. The addition of a front recirculation port that can be used in transport mode keeps all the components hot resulting in less down time.

High Quality Heated Hose System:

Cimline's heated hose is designed and manufactured in house right here in the USA and is built for demanding high use applications in the most challenging environments. The higher voltage generator powering the M1 and M2 heated hose, which is now standard, reaches full temperature in just 30 minutes.

Quiet and Uncomplicated:


Contractors around the world give high praise over the lower loading height, low noise operation, simple automated control systems and overall operator comfort of the Cimline M-Series crack sealers.



800-328-3874
CIMLINE.COM



Front and rear recirculation ports



19hp Isuzu tier IV diesel power plant



M4 with dual pump/dual hose option



External heated 20 gpm material pump



Variable material pump flow control



Convenient control panel and key switch

SPECIFICATIONS

Cimline M-Series	M1 #311-001-902	M2 #311-021-902	M4 #301497
Material Capacity	150 Gallons	230 Gallons	410 Gallons
Tank Burner Heat Rating	250,000 BTU's	290,000 BTU's	400,000 BTU's
Heat Transfer Oil Capacity	22 Gallons	30 Gallons	42 Gallons
Tank Insulation	Fiberglass, 1.5 Inch Thickness		
Heating Method	Beckett Diesel Fired Burner		
Diesel Fuel Capacity	33 Gallons		
Hydraulic Capacity	33 Gallons		
Engine	Isuzu Tier IV 19HP Diesel		
Temperature Gauge	Electronic Control and 5 Inch Analog		
Material Loading Height	49 Inches	50 Inches	54 Inches
Material Loading Doors	Single Curbside	Dual (Both Sides)	Dual (Both Sides)
Material Pump Rate	20 GPM	20 GPM	20 GPM
GVWR	5,515 Lbs.	6,700 Lbs.	9259 Lbs.
GAWR	7,000 Lbs.	7,000 Lbs.	10,000 Lbs.
Axles	1x7,000 Torsion Type	2x3,500 Torsion Type	2x5,000 Torsion Type
Trailer Brake Type	Electric	Electric	Electric
Dimensions (LxWxH)	170 x 83 x 93 Inches	170 x 82 x 91 Inches	189 x 87 x 84 Inches
Shipping Weight	4,200 Lbs.	4,750 Lbs.	6,175 Lbs.
Warranty	1 Year Bumper to Bumper		

Due to continuous improvement, specifications are subject to change without notice.



Learn more at cimline.com
 Phone : 800-328-3874 Email : orders@cimline.com

PRODUCTS FROM CIMLINE



ME3
Mastic Melter Machine



P2 Two-Person Patcher with
DuraPatcher™ Technology



X2 Carry On
Air Compressor