



**INNOVATION
IN PRESERVATION**



M-Series Skid-Mount

The reputation of the MAGMA for simple, safe, sustainable operation lives on with the M-Series which marks a new chapter for Cimline™ with signature safety green paint. Going green means more than a paint color change as the M-Series comes standard with lower emissions, lower fuel consumption and quieter operation for a better work environment. M-Series's most popular features of the low-profile design, high production and easy to use operator features continue to make Cimline™ the leader in crack sealing.

M-SERIES FAMILY

M1™
150 Gallons of
Material Capacity



M2™
230 Gallons of
Material Capacity



M4™
410 Gallons of
Material Capacity



Ergonomic Simplicity:

M-Series offers the highest levels of operator comfort with a completely redesigned delivery system. The no-stress boom swivels around the heated sealing hose, unlike any other machine, minimizing hose stress and providing the industry-leading operating range. Add the new heated wand option for even better comfort and ease of use.

Community and Operation Friendly:

The clean Tier IV compliant diesel engine runs at lowest possible RPM for the best combination of performance and fuel economy. The standard noise abatement muffler, when combined with the engine cover option, reduces noise levels up to 40% when compared to other models.

Simple-Seal Controller:

Simple-Seal is the next generation of digital control providing the easiest operation yet. Simply set the mode switch to "RUN". When the (3) Green LED's come on, start working. At the end of the day set mode switch to "CLEAN OUT" run for 2 minutes and set mode switch to "OFF". The control box never needs to be opened for normal operation.

800-328-3874
CIMLINE.COM



Stress-free boom rotates around hose



Electric heated wand option



Optional heated draw-off option



Optional engine cover



Simple seal controller



Can be mounted on trailer or vehicle

SPECIFICATIONS

Material Capacity gal. (liters)	150 (568)
Engine HP	25 Diesel
Heating Method	Diesel
Heat Rating BTUs	250,000
Material Pump GPM (LPM)	20 (76)
Heated Hose Length- ID ft. (m)	20 (6.1) - 0.75 (19.05)
Loading Doors	Single Curbside
Fuel Capacity gal. (liters)	33 (125)
Hydraulic Capacity gal. (liters)	33 (125)
Heat Transfer Oil gal. (liters)	22 (83)
Dimensions L x W x H in. (L x W x H cm.)	140 x 77 x 85 (356 x 196 x 216)
Shipping Weight lbs. (kg)	4,120 (1,869)
Warranty	One Year

Due to continuous improvement, specifications are subject to change without notice.

PRODUCTS FROM CIMLINE



C1™ Combination Mastic/Crack Sealer Melter Applicator



R3™ Asphalt Crack Router with Dust Control



X2™ Carry-on Compressor



Learn more at cimline.com
Phone : 800-328-3874 Email : orders@cimline.com