



**INNOVATION
IN PRESERVATION**

P3

Truck Mounted Patcher with DuraPatcher™ Technology



Truck Mounted Convenience:

The same features as the trailer patcher but with truck-mounted convenience. Especially useful in low clearance residential streets or areas with tight turning radii. The 6 yd aggregate hopper keeps operators out working with fewer refills. The Universal design easily mounts to most truck chassis.

A Permanent Patch in 4 Easy Steps:

Patch in almost any weather conditions and eliminate labor-intensive, poor-performing patches with the DuraPatcher 4 step process.




1. Clean:

Use high volume low pressure air to clean the patch of debris.



2. Tack:

Prep the patch with a coating of emulsion.



3. Fill:

Inject emulsion coated aggregate and fill pothole.



4. Coat:

Apply a light coating of clean aggregate and open to traffic.

Ergonomic No-Stress Boom:

The three piece boom provides the ultimate support and near effortless and accurate delivery hose positioning by the operator. The boom easily rotates throughout its entire 18-foot working radius allowing for long reach and greater productivity with fewer truck moves to reach the work area.

Vent-Flo Nozzle:

The specially designed Vent-Flo nozzle properly coats the aggregate with the right amount of emulsion regardless of aggregate size. The mix is applied at an angle to the repair allowing maximum placement and best operator safety. The vent holes diffuse/slow down the air stream to minimize rock overspray and maximize placement into the repair.

Heated Emulsion Tank:

The Emulsion Tank provides enough product to apply over 10 tons of patch before refilling. The heating blankets allow the patcher to be plugged in to keep emulsion at a “ready-to-go” temperature.

800-328-3874
CIMLINE.COM



Vent-Flo™ Nozzle And Optional Heater



Six Yard Gravity Rock Hopper Capacity



Hopper Vibrator



Ergonomic No-Stress Boom



Simple And Easy Hand Controls



Hopper Heating System

SPECIFICATIONS

Cimline P3 #301531

Emulsion Capacity	250 US Gallons
Aggregate Capacity	6 Yards Gravity Fed
Tank Gravity Drain	3 Inch with Brass Ball Valve
Analog Tank Temperature Gauge	5 Inch
Tank Heating Method (Overnight)	Electric Blanket
Tank Heat Rating	2 x 1500w (110v @ 15a)
Tank Insulation	Fiberglass, R15
Patcher Engine	74HP IT4 Diesel
Patcher Engine Fuel Capacity	18 Gallons
Blower	450 CFM, 10 PSI @ 1500 RPM
Clean Out/Solvent Capacity	13 Gallons
Construction	10 Inch Channel Main Frame
Patcher Dimensions (LxWxH)	241 x 92 x 76 Inches
Patcher Shipping Weight	9,550 Lbs.
GVWR	N/A
Axles/Suspension	N/A
Brake Type	N/A
Warranty	1 Year

PRODUCTS FROM CIMLINE



M2 230 Gallon Crack Sealer Melter Applicator



P5 One-Person Patcher with DuraPatcher Technology™



T-Series Stationary Tanks

Due to continuous improvement, specifications are subject to change without notice.



Learn more at cimline.com
Phone : 800-328-3874 Email : orders@cimline.com