



**INNOVATION
IN PRESERVATION**

P4

J-Hook Mounted Patcher with DuraPatcher™ Technology



Eliminate Seasonality in Your Fleet:

Utilize your existing Hook Lifts and add the proven effectiveness of spray injection to permanently repair potholes and washouts. The self-contained hook lift P4 can be loaded on the truck in minutes for two-person patching. In national tests, spray-injection patching has ranked highest for the lowest cost per patch and longest lasting versus all other methods.

A Permanent Patch in 4 Easy Steps:

Patch in almost any weather conditions and eliminate labor intensive, poor performing patches with the DuraPatcher.



1. Clean:
Use high volume low pressure air to clean the patch of debris.



2. Tack:
Prep the patch with a coating of emulsion.



3. Fill:
Inject emulsion coated aggregate and fill pothole.



4. Coat:
Apply a light coating of clean aggregate and open to traffic.

Ergonomic No-Stress Boom:

The 3 piece boom design provides the ultimate in support for the operator moving the delivery hose. Easily covers an 18-foot working radius allowing for smooth patching anywhere in the work zone.

Vent-Flo Nozzle:

The specially designed Vent-Flo nozzle properly coats the aggregate with the right amount of emulsion regardless of aggregate size. The mix is applied at an angle to the repair allowing maximum placement and best operator safety. The vent holes diffuse/slow down the air stream to minimize rock overspray and maximize placement into the repair.

Heated Emulsion Tank:

The Emulsion Tank provides enough product to apply over 10 tons of patch before refilling. The heating blankets allow the patcher to be plugged in to keep emulsion at a “ready-to-go” temperature.

800-328-3874
CIMLINE.COM



Rollers Allow Easy Loading And Unloading



Six Yard Gravity Rock Hopper Capacity



Hopper Vibrator



Ergonomic No-Stress Boom



Simple And Easy Hand Controls



Hopper Heating System

SPECIFICATIONS

Cimline P4 #408085

Emulsion Capacity	250 US Gallons
Aggregate Capacity	6 Yards Gravity Fed
Tank Gravity Drain	3 Inch with Brass Ball Valve
Analog Tank Temperature Gauge	5 Inch
Tank Heating Method (Overnight)	Electric Blanket
Tank Heat Rating	2 x 1500w (110v @ 15a)
Tank Insulation	Fiberglass, R15
Patcher Engine	74HP Tier IV Final Diesel
Patcher Engine Fuel Capacity	18 Gallons
Blower	450 CFM, 10 PSI @ 1500 RPM
Clean Out/Solvent Capacity	13 Gallons
Construction	10 Inch Channel Main Frame
Patcher Dimensions (LxWxH)	Approx. 241x92x76 Inches (Build Spec. Dependent)
Patcher Shipping Weight	Approx. 9,000 Lbs. (Build Spec. Dependent)
GVWR	N/A
Axles/Suspension	N/A
Brake Type	N/A
Warranty	1 Year

Due to continuous improvement, specifications are subject to change without notice.



Learn more at cimline.com
Phone : 800-328-3874 Email : orders@cimline.com

PRODUCTS FROM CIMLINE



ME3 Mastic Sealer Melter Applicator



P5 One-Person Patcher with DuraPatcher Technology™



T-Series Stationary Tanks